AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

Claim 35. (Previously Presented) An image recording apparatus having a copy mode and a facsimile mode, the image recording apparatus comprising:

a panel which has input keys operable to input a numerical value corresponding to at least one of a number of copies in the copy mode and a telephone number of a destination in the facsimile mode;

a display which selectively displays one of a screen for the copy mode and a screen for the facsimile mode, a display capacity of the screen in the copy mode being smaller than a display capacity of the screen in the facsimile mode; and

a controller which, when the copy mode is set and when the numerical value input by the panel exceeds the display capacity of the screen in the copy mode, switches from the copy mode to the facsimile mode.

Claim 36. (Previously Presented) The image recording apparatus according to claim 35, wherein the display capacity of the screen, when the input numerical value corresponding to the number of copies is displayed, is smaller than the display capacity of the screen, when the input numerical value corresponding to the telephone number of the destination is displayed.

Claim 37. (Previously Presented) An image recording apparatus having a copy mode and a facsimile mode, the image recording apparatus comprising:

a panel which has input keys operable to input a numerical value corresponding to at least one of a number of copies in the copy mode and a telephone number of a destination in the facsimile mode, and which has a start key which starts at least one of copying and facsimile transmission; and

a controller which determines whether or not the numerical value input by the panel exceeds a predetermined number of digits of the numerical value corresponding to the number of copies when the copy mode is set, and which, when the numerical value input by the panel exceeds the predetermined number of digits of the numerical value corresponding to the number of copies and when the start key is actuated, maintains the copy mode and inhibits starting copying;

the controller further being configured to wait for another input by the panel in the copy mode, when the controller inhibits copying.

Claim 38. (Previously Presented) The image recording apparatus according to claim 37, wherein the controller determines that the input numerical value corresponds to the number of copies by using, as a threshold value, a number of digits less than the number of digits utilized for the telephone number of the destination.

Claim 39. (Previously Presented) The image recording apparatus according to claim 37, wherein the another input by the panel comprises an input of a reset key.

Claim 40. (Previously Presented) An image recording apparatus having a copy mode and a facsimile mode, the image recording apparatus comprising:

a panel which has input keys operable to input at least a numerical value corresponding to one of the number of copies in the copy mode and a telephone number of a destination in the facsimile mode; and

a controller which determines, when the copy mode is set, whether or not an input by the panel during the input of the numerical value corresponding to the number of copies includes a predetermined character and which switches from the copy mode to the facsimile mode when the input by the panel during the input of the numerical value corresponding to the number of copies includes the predetermined character, the predetermined character not including a numerical value.

Claim 41. (Previously Presented) The image recording apparatus according to claim 40, wherein the predetermined character comprises a pause.

Claim 42. (Previously Presented) The image recording apparatus according to claim 40, wherein when the controller switches from the copy mode to the facsimile mode, the numerical value input by the panel is retained, the retained numerical value being utilized in the facsimile mode.

Claim 43. (Previously Presented) The image recording apparatus according to claim 42, wherein the controller combines digits of a numerical value input by the panel in the facsimile mode with digits of the retained numerical value, after the controller switches from the copy mode to the facsimile mode, and calls the destination based on the telephone number including the retained numerical value.

Claim 44. (Previously Presented) A method for controlling an image recording apparatus having a copy mode and a facsimile mode, the method comprising:

inputting a numerical value corresponding to at least one of a number of copies in the copy mode and a telephone number of a destination in the facsimile mode;

selectively displaying one of a screen for the copy mode and a screen for the facsimile mode, a display capacity of the screen in the copy mode being smaller than a display capacity of the screen in the facsimile mode;

setting the copy mode; and

switching from the copy mode to the facsimile mode, when the input numerical value exceeds the display capacity of the screen in the copy mode.

Claim 45. (Previously Presented) A method for controlling an image recording apparatus having a copy mode and a facsimile mode, the image recording apparatus having a start key which starts at least one of copying and facsimile transmission, the method comprising:

inputting a numerical value corresponding to at least one of a number of copies in the copy mode and a telephone number of a destination in the facsimile mode;

determining whether or not the input numerical value exceeds a predetermined number of digits of a numerical value corresponding to the number of copies when the copy mode is set;

inhibiting of the copying when the input numerical value exceeds the predetermined number of digits of the numerical value corresponding to the number of copies, even if the start key is actuated; and

waiting for another input in the copy mode when copying is inhibited, the copy mode being maintained when copying is inhibited.

Claim 46. (Previously Presented) A method for controlling an image recording apparatus having a copy mode and a facsimile mode, the method comprising:

inputting a numerical value corresponding to at least one of the number of copies in the copy mode and a telephone number of a destination in the facsimile mode;

determining, when the copy mode is set, whether or not the input includes a predetermined character during input of the numerical value corresponding to the number of copies;

switching from the copy mode to the facsimile mode when the input includes the predetermined character during input of the numerical value corresponding to the number of copies, the predetermined character not including the numerical value.

Claim 47. (Previously Presented) The image recording apparatus according to claim 35, wherein the controller is configured to switch to the facsimile mode in response to the numerical value exceeding the display capacity of the screen in the copy mode.

Claim 48. (Previously Presented) The method for controlling according to claim 44, wherein the switching is in response to the input numerical value exceeding the display capacity of the screen in the copy mode.

Claim 49. (New) The image recording apparatus according to claim 35, said display comprising a single display region having a display capacity that changes in accordance with one of the copy mode and the display facsimile mode.

Claim 50. (New) The method for controlling an image recording apparatus according to claim 44, the selective displaying comprising:

changing a display capacity of a single display region in accordance with one of the copy mode and the facsimile mode.

Claim 51. (New) The method for controlling an image recording apparatus according to claim 46, wherein, upon switching from the copy mode to the facsimile

mode, the input numerical value is retained, the retained numerical value being utilized in the facsimile mode.

Claim 52. (New) The method for controlling an image recording apparatus according to claim 51, further comprising combining digits of a numerical value input in the facsimile mode with digits of the retained numerical value, upon switching from the copy mode to the facsimile mode, and calling the destination based on the telephone number including the retained numerical value.

SUMMARY AND CONCLUSION

By the above amendment, claim 49 has been amended to clarify the language thereof. The claim amendment does not further limit or narrow the claim.

Any amendments to the claims which have been made in this amendment, and which have not been specifically noted to overcome a rejection based upon the prior art, should be considered to have been made for a purpose unrelated to patentability, and no estoppel should be deemed to attach thereto.

If there should be any questions, the Examiner is invited to contact the undersigned at the telephone number listed below.

Respectfully submitted,

Masanori-KAMATA

William Pieprz Reg. No. 33,630

Bruce H. Bernstein Reg. No. 29,027

December 15, 2005 GREENBLUM & BERNSTEIN, P.L.C. 1950 Roland Clarke Place Reston, VA 20191 (703) 716-1191